

Package: DIDmultiplegt (via r-universe)

October 7, 2026

Type Package

Title Estimators DID with Multiple Groups and Periods

Version 2.1.0

Maintainer Anzony Quispe <anzony.quispe@gmail.com>

Description Estimators of Difference-in-Differences based on de Chaisemartin and D'Haultfoeuille.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

URL https://github.com/Credible-Answers/did_multiplegt

Depends R(>= 3.4.0)

Imports dplyr (>= 1.0.0), fixest (>= 0.6.0), plotrix, sampling, stats, parallel, stringr, rlang, DIDmultiplegtDYN, DIDHAD

Suggests polars

Author Anzony Quispe [aut, cre], Diego Ciccio [aut], Felix Knau [aut], Mélitine Malezieux [aut], Doulo Sow [aut], Shuo Zhang [aut], Clément de Chaisemartin [aut]

RoxygenNote 7.3.3

Additional_repositories <https://rpolars.r-universe.dev>

Config/pak/sysreqs cmake make libicu-dev libx11-dev zlib1g-dev

Repository <https://credible-answers.r-universe.dev>

Date/Publication 2026-07-09 14:28:22 UTC

RemoteUrl https://github.com/credible-answers/did_multiplegt

RemoteRef HEAD

RemoteSha 70cbc6b51710b4b81993607b6975bc7bd21a0c70

RemoteSubdir R

Contents

did_multiplegt	2
wagepan_mgt	3

Index	5
--------------	----------

did_multiplegt	<i>Main function</i>
----------------	----------------------

Description

Library of Estimators in Difference-in-Difference (DID) designs with multiple groups and periods.

Usage

```
did_multiplegt(mode, ...)
```

Arguments

mode	("dyn", "had", "old") Estimator selector. The dyn mode calls did_multiplegt_dyn , the had mode calls did_had and the old mode calls did_multiplegt_old .
...	Options passed to specified estimator. For more details on allowed options, check out the command-specific documentation: did_multiplegt_dyn , did_had , did_multiplegt_old .

Overview

did_multiplegt wraps in a single command all the estimators from de Chaisemartin and D'Haultfoeuille. Depending on the mode argument, this command can be used to call the following estimators.

[did_multiplegt_dyn](#). In dyn mode, the command computes the DID event-study estimators introduced in de Chaisemartin and D'Haultfoeuille (2024a). This mode can be used both with a binary and staggered (absorbing) treatment and a non-binary treatment (discrete or continuous) that can increase or decrease multiple times. The estimator is also robust to heterogeneous effects of the current and lagged treatments. Lastly, it can be used with data where the panel st is unblanced or more disaggregated than the group level.

[did_had](#). In had mode, the command computes the DID estimator introduced in de Chaisemartin and D'Haultfoeuille (2024b). This mode estimates the effect of a treatment on an outcome in a heterogeneous adoption design (HAD) with no stayers but some quasi stayers.

[did_multiplegt_old](#). In old mode, the command computes the DID estimators introduced in de Chaisemartin and D'Haultfoeuille (2020). This mode corresponds to the old version of the did_multiplegt command. Specifically, it can be used to estimate DID_M , i.e. the average across t and d of the treatment effects of groups that have treatment d at $t - 1$ and change their treatment at t , using groups that have treatment d at $t - 1$ and t as controls. This mode could also be used to compute event-study estimates, but we strongly suggest to use the dyn mode, since it is way faster and includes comprehensive estimation and post-estimation support.

References

de Chaisemartin, C and D’Haultfoeuille, X (2020). American Economic Review, vol. 110, no. 9. **Two-Way Fixed Effects Estimators with Heterogeneous Treatment Effects.**

de Chaisemartin, C and D’Haultfoeuille, X (2024a). Review of Economics and Statistics, 1-45. **Difference-in-Differences Estimators of Intertemporal Treatment Effects.**

de Chaisemartin, C and D’Haultfoeuille, X (2024b). **Two-way Fixed Effects and Differences-in-Differences Estimators in Heterogeneous Adoption Designs.**

Vella, F. and Verbeek, M. 1998. Journal of Applied Econometrics 13(2), 163–183. **Whose wages do unions raise? a dynamic model of unionism and wage rate determination for young men.**

Examples

```
# Test all modes using Vella and Verbeek (1998) data:
data("wagepan_mgt")
wagepan_mgt$X <- runif(n=nrow(wagepan_mgt)) * (wagepan_mgt$year >= 1983)
Y = "lwage"
G = "nr"
T = "year"
D = "union"
X = "X"

did_multiplegt(mode = "old", wagepan_mgt, Y, G, T, D)
## Not run:
# These examples require polars package to be installed
did_multiplegt(mode = "dyn", wagepan_mgt, Y, G, T, D, graph_off = TRUE)
did_multiplegt(mode = "had", wagepan_mgt, Y, G, T, X, graph_off = TRUE)

## End(Not run)
```

wagepan_mgt	wagepan_mgt
-------------	-------------

Description

A subset of data from Vella and Verbeek (1998).

Usage

wagepan_mgt

Format

- ## ‘wagepan_mgt’ A data frame with 4,360 rows and 5 columns:
- lwage** Log wage.
- nr** Worker ID.
- year** Year
- union** Union status.
- hours** Annual Hours worked.

Source

<<http://fmwww.bc.edu/ec-p/data/wooldridge/wagepan.des>>

Index

* **datasets**

wagepan_mgt, [3](#)

did_had, [2](#)

did_multiplegt, [2](#)

did_multiplegt_dyn, [2](#)

did_multiplegt_old, [2](#)

wagepan_mgt, [3](#)